

Refresher

UVElite[®]
RESILIENT RESTORATION

Use Refresher for periodic maintenance of resilient floors coated with UVElite finish. Refresher contains lacquer particles designed to add an extra layer of protection and shine to high-traffic areas that have become worn.

ADVANTAGES

- **Use As Needed** - Modern maintenance for top-coated resilient floors.
- **No Buildup** - Does not build up layers and dissolves itself with each new application.
- **Keeps Floors Looking Great** - Prevents the floor from visual signs of aging, wear and micro-scratches.

DIRECTIONS FOR USE

PREPARATION

Before applying Refresher, ensure that floor has not been treated with wax or polish. Then, remove all loose particles, dust, and contamination with a non-treated dust mop or vacuum. Use UVElite's Cleaner and a microfiber mop to clean the floor surface effectively.

APPLICATION

Spray Refresher directly on the floor. Disperse Refresher immediately with a clean, damp mop or lint-free cloth. Do not dilute Refresher. Make sure to overlap areas so the entire floor is covered completely and consistently. Allow floor to dry thoroughly, usually in one hour. To maintain the look and the protective properties of topcoated floors, we recommend an application of Refresher on heavy traffic areas after about every fifth cleaning with UVElite Cleaner.

HEALTH & ENVIRONMENT

In case of eye contact, flush with plenty of water. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. Read all information this technical data sheet, on the label and on the Material Safety Data Sheet. Please do not pour surplus Refresher down the drain. Dispose of it in accordance with local regulations.

KEEP FROM FREEZING!
DO NOT TAKE INTERNALLY!
KEEP OUT OF REACH OF CHILDREN!

TECHNICAL DATA

CONTENT	Acrylic dispersion and ammonia
SOLIDS BY VOLUME	4%
COVERAGE	approx. 60 m ² (650ft ²) per jug
DRY TIME	1-2 hours
pH	approx. 8.5
PACKAGING	6 x 1 liter (1.05 quart) jugs per box
STORAGE	Store between temperatures of 5-25°C (40-80°F). Protect from freezing.
SHELF LIFE	Best before 12 months from date of manufacture in unopened original packaging under recommended storage condition.
CLEAN UP	Clean tools with water, before Refresher has dried.

TECHNICAL ASSISTANCE

Contact your distributor or
UVElite Technical Service

Europe HQ

Olof Wijksväg 9,
444 65 Jörlanda, Sweden
+46 303 376 300

North America

8400 East Crescent Pkwy - 6th Floor
Greenwood Village, CO 80111, USA
+1 (877) 416-5972

info@uvelite.com
www.uvelite.com

